

MX-miditube deco opbouw



LED HUY S

COMFORT DUURZAAM ENERGIEZUINIG



IP20



BODY MAT AL / PC



50-60Hz

50000h
L80 B20

2 MacAdam



30°



+




200

Ø72,5

LED 2700K / CRI80						
CREE	7W	570 lm	100-240V	-	04.01.0688	☐
	7W	570 lm	100-240V	-	04.01.0687	☒
	7W	570 lm	220-240V	PHASE CUT ▲ MAINS LC	04.01.0684	☐
	7W	570 lm	220-240V	PHASE CUT ▲ MAINS LC	04.01.0683	☒
3000K / CRI80						
N	7W	620 lm	100-240V	-	04.01.0686	☐
	7W	620 lm	100-240V	-	04.01.0685	☒
	7W	620 lm	220-240V	PHASE CUT ▲ MAINS LC	04.01.0682	☐
	7W	620 lm	220-240V	PHASE CUT ▲ MAINS LC	04.01.0681	☒
4000K / CRI80						
N	7W	660 lm	100-240V	-	04.11.0674	☐
	7W	660 lm	100-240V	-	04.11.0675	☒
	7W	660 lm	220-240V	PHASE CUT ▲ MAINS LC	04.11.0676	☐
	7W	660 lm	220-240V	PHASE CUT ▲ MAINS LC	04.11.0677	☒

LED 2700K / CRI80						
CREE	13W	1240 lm max.	100-240V	-	04.01.0680	☐
	13W	1240 lm max.	100-240V	-	04.01.0679	☒
	13W	1240 lm max.	220-240V	PHASE CUT ▲ MAINS LC	04.01.0676	☐
	13W	1240 lm max.	220-240V	PHASE CUT ▲ MAINS LC	04.01.0675	☒
3000K / CRI80						
N	13W	1330 lm max.	100-240V	-	04.01.0678	☐
	13W	1330 lm max.	100-240V	-	04.01.0677	☒
	13W	1330 lm max.	220-240V	PHASE CUT ▲ MAINS LC	04.01.0674	☐
	13W	1330 lm max.	220-240V	PHASE CUT ▲ MAINS LC	04.01.0673	☒
4000K / CRI80						
N	13W	1330 lm max.	100-240V	-	04.11.0670	☐
	13W	1330 lm max.	100-240V	-	04.11.0671	☒
	13W	1330 lm max.	220-240V	PHASE CUT ▲ MAINS LC	04.11.0672	☐
	13W	1330 lm max.	220-240V	PHASE CUT ▲ MAINS LC	04.11.0673	☒

NOT INCLUDED




04.01.0672

04.01.0671



20



04.01.0670

04.01.0669



20

+ NOT INCLUDED / REQUIRED



DIF MAT PC



04.01.1404

04.01.1403

04.01.1402



NOT INCLUDED



04.01.1398



04.11.1398

5