

OX-Gea Power Led



LED HUYS

COMFORT DUURZAAM ENERGIEZUINIG



® IP67 IK10

BODY MAT INOX AISI 316 AL / TEC. POLI

CA



100-240V

50-60Hz



GLA

50000h L70 B30


3 MacAdam



<40°C ±15°



1800Kg.




LED	3000K / CRI85				
LUMILEDS	6W	522 lm	25°	04.01.2567	
	4000K / CRI85				
	6W	549 lm	25°	04.01.2566	
					12 81

INCLUDED



DIFFUSER FILTER 45°




LED	3000K / CRI85				
LUMILEDS	6W	522 lm	25°	04.01.2550	
	4000K / CRI85				
	6W	549 lm	25°	04.01.2551	
					12 81

INCLUDED



DIFFUSER FILTER 45°



LED	3000K / CRI85				
LUMILEDS	9W	873 lm	16°	04.01.2553	
	18W	1566 lm	16°	04.01.2555	
	4000K / CRI85				
	9W	918 lm	16°	04.01.2552	
	18W	1647 lm	16°	04.01.2556	
					2 56

INCLUDED



DIFFUSER FILTER 34°

NOT INCLUDED




04.01.2642

BODY MAT PP 20

Caja de empotrar específica para techos de hormigón.
 Flush-mounted box for concrete ceilings.
 Boîtier à encastrer spécial plafonds en béton.
 Spezifisches Einbauehäuse für Betondecken.
 Scatola per incasso specifica per soffitti in calcestruzzo.
 Caixa de encastrar específica para tectos de betão.
 Специальная монтажная коробка для бетонных потолков.
 Specjalna skrzynka do wbudowania dla betonowych sufitów.


Photometric data

LED 6W 4000K




D(m)	MedLux	H(m)
2.15	35	5
1.72	54	4
1.29	97	3
0.86	218	2
0.43	872	1

LED 9W 4000K



D(m)	MedLux	H(m)
1.43	177	5
1.14	276	4
0.86	491	3
0.57	1105	2
0.29	4420	1

LED 18W 4000K



D(m)	MedLux	H(m)
1.39	276	5
1.12	432	4
0.84	768	3
0.56	1728	2
0.28	6910	1